Mobil 1 Engine Oils

Additional product information, including Product Data Sheets and this chart, is available at Mobiloil.com

7/5/11

7/5/11										1		
		Nominal	Nominal			API, ILSAC, and Other		1	Ford		I	
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Service Fill	МВ	BMW	vw
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	-	ACEA	Fill Approval		Approval	Approval	Approval
				Boosted, advanced full synthetic								
				formula designed for today's								
Mobil 1				longer oil change intervals in								
Extended				Honda, Chryslers and newer	Vehicles that require 5W-		A1/B1-08					
Performance	5W-20	800	900	Toyotas	20	GF-5,SN	A1/B1-10		Х			
				Boosted, advanced full synthetic								
				formula designed for today's								
Mobil 1				longer oil change intervals in			A1/B1-08, A5/B5					
Extended				many domestic, including GM,	Vehicles that require 5W-	GF-5,SN	08, A1/B1-10,					
Performance	5W-30	800	900	and imported vehicles.	30 or 10W-30.	Honda HTO-06	A5/B5-10	dexos1	Х			
Mahila				Boosted, advanced full synthetic								
Mobil 1				formula designed for today's			A1/B1-08, A5/B5					
Extended	1014/ 20	000	000	longer oil change intervals in	Vehicles that require 5W-		08, A1/B1-10,					
Performance	10W-30	800	900	many domestics and imports.	30 or 10W-30.	GF-5,SN	A5/B5-10					
	0W-20			Advanced full synthetic	Most vehicles that specify							
	Advanced			formulation designed for	0W-20 (newer Toyotas							
	Fuel			enhanced fuel economy and cold	and Hondas), 5W-20 and		A1/B1-08,					
Mobil 1	Economy	650	750	weather performance.	certain hybrids.	GF-5,SN	A1/B1-08,		х			
	0W-30	030	750	Advanced full synthetic	centain hybrids.	01-5,511	AI/DI-IU		~			
	Advanced			formulation designed for								
	Fuel			enhanced fuel economy and cold	Most vehicles that specify		A1/B1-10.					
Mobil 1	Economy	650	750	weather performance.	5W-30 or 10W-30.	GF-5,SN	A5/B5-10		х			
						0. 0,0.1						
				Advanced full synthetic	Porsche.	Chrysler						
				formulation designed to meet the	Many European vehicles.	MS10850,						
				requirements of many European	HT/TS applications.	Nissan GT-R	A3/B3-08, A3/B4			229.3/		502.00 /
Mobil 1	0W-40	1000	1100	vehicles.		SN,SM,SL,SJ	08			229.5	Longlife 01	505.00
				Advanced full synthetic								
				formulation designed to meet the								
				requirements of many newer								
				vehicles including Hondas, Fords,	Vehicles that require 5W-		A1/B1-08, A1/B1					
Mobil 1	5W-20	800	900	Chryslers and newer Toyotas.	20.	GF-5,SN	10,		Х			
				Advanced full synthetic								
				formulation designed to meet the			A1/B1-08,					
				requirements of many domestic,			A5/B5-08,					
				including GM, and imported	Vehicles that require 5W-	GF-5,SN	A1/B1-10,					
Mobil 1	5W-30	800	900	vehicles.	30. Corvette approved.	Honda HTO-06	A5/B5-10	dexos1	Х			
				Higher viscosity, advanced full	Daracha		40/00.00					504.04
Mahild	F14/ 50	1000	1400	synthetic formula designed for	Porsche.	ON/ON4	A3/B3-08,			000 4 /000 0		501.01,
Mobil 1	5W-50	1000	1100	performance vehicles	HT/HS applications.	SN/SM	A3/B4-08			229.1 /229.3		505.00
	1						A1/B1-08,					
	1			Advanced full synthetic formula	Vahieles that as mine first		A5/B5-08,					
Mobil 1	1014/20	800	000	designed for domestics and	Vehicles that require 5W-		A1/B1-10,					,
Mobil 1	10W-30	800	900	imports Reasted higher viscosity	30 or 10W-30.	GF-5,SN	A5/B5-10					\
				Boosted, higher viscosity, advanced full synthetic formula	UT/US applications							
	1				HT/HS applications.		A3/B3-08, A3/B4					
Mobil 1	15/0/ 50	1200	1200	designed for performance	Racing and Flat tappet	SN/SM	A3/B3-08, A3/B4 08, A3/B3-10]				
Mobil 1	15W-50	1200	1300	vehicles.	applications.	211/21VI	U8, A3/B3-10					
				Advanced full synthetic formula	Most diesel applications.	CJ-4, CI-4,						
Mobil 1 Turbo	1			designed for diesel powered pick-	including engines with	CI-4 Plus, SM,						
Diesel Truck	5W-40	1100	1200	ups and trucks.	diesel particulate filters.	SL	E7					
DIESEI ITUUK	577-40	1100	1200	upo anu nucko.	uiesei particulate iliteis.	3L	C/	l	I			L

		Nominal	Nominal			API, ILSAC, and Other			Ford			
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Service Fill	MB	BMW	VW
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
							A1/B1-08,					
				Boosted, advanced full synthetic			A5/B5-10,					
Mobil 1 High				formula designed for higher	Vehicles that require 5W-		A1/B1-10,					
Mileage	5W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A5/B5-10					
				Boosted, advanced full synthetic								
Mobil 1 High				formula designed for higher	Vehicles that require 5W-		A3/B3-08, A3/B4					
Mileage	10W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	08, A3/B3-10					
				Boosted, advanced full synthetic								
Mobil 1 High				formula designed for higher	Higher viscosity		A3/B3-08, A3/B4					
Mileage	10W-40	1000	1100	mileage vehicles.	applications.	SN/SM/SL/SJ	08, A3/B3-10					
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.							
Mobil 1 ESP				passenger car diesels that have	Available at most MB					229.31,		
Formula M	5W-40	800	900	particulate filters.	dealers.	None				229.51		
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.							
Mobil 1 ESP				passenger car diesels that have	Available at many	Chrysler MS-				229.31,		
Formula	5W-30	800	900	particulate filters.	Chrysler dealers.	11106	C3-08, C2-08			229.51	Longlife-04	504/507
				Advanced full synthetic formulas								
				designed specifically for		SM, SJ, SH,						
Mobil 1 Racing				motorcycles where clutch	All motorcycles where	JASO MA1						
4T	10W-40	1200	1300	lubrication is also important.	10W-40 is specified	2006	-					
				Advanced full synthetic formulas	All motorcycles where							
				designed specifically for	20W-50 is specified,							
				motorcycles where clutch	especially V-Twin							
Mobil 1 V-Twin	20W-50	1600	1700	lubrication is also important.	engines	SJ						
				Advanced full synthetic formula								
				specifically designed to maximize	0							
				horsepower under race	recommended for street							
Mobil 1 Racing	0W-30	1750	1850	conditions.	use.							
				Advanced full synthetic formula								
				specifically designed to maximize	0							
				engine protection under race	recommended for street							
Mobil 1 Racing	0W-50	1750	1850	conditions.	use.							

** API SH and API SG are no longer licensable. ***For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets which are available online at www.mobiloil.com.